



parqwood XXL long

strong wood floors • strong wood floors

BERRY  ALLOC



albatre




nude



silk



nature



ambre



real
wood



water
resistance
7 - 10%



durable &
strong
class 33



10 times less
use of wood



healthy
interior




20 years
residential
warranty



Clear
Grade (A)



parqwood XXL long



product description

Bevel	-	2
Oak layer thickness (+0/-0,1)	mm	0,6
Residential use guarantee	-	20 years
Class of use	ISO 10874	23 (heavy domestic use) 33 (heavy commercial use)
Total thickness	mm	10
Total weight	kg / m ²	8,5
Format	mm	210 x 2200
Pack content	-	6 planks (25.02 kg, 2.772 m ²)
Pallet content	-	40 packs
Pallet size (h x w x l)	mm	750 x 960 x 2220

tests results

Moisture level	-	7 - 10%
Installation system	-	BestLoc X-Treme
Surface treatment	-	Ultimtec high performance varnish
Resistance to abrasion	XP B 53-669	> 15 000 rev. (TT CS10)
Gloss level	Gloss 60	5+/-2 (matt)
Compatibility with underfloor heating	-	Compatible with electric radiant floor heating (max 90 W/m ²) and low-temperature hot water heating system (see conditions)
Thermal resistance	m ² K/W	0,052
Fire resistance	EN 13501-1 (oak)	Cfl-s1
CE marking	EN 14342	CE
Formaldehyde emissions	EN 717-1	E1
VOC emissions	ISO 16000-9	M1 / A+
Environmental programme	Certification	PEFC/10-31-1047

2200 (L) x 210 (W)mm

made in France